

Inquiry form for the SKG-service lift **ISO-PE EASY 1500/2000**

Goods lift with one accompanying person / Swing doors serving at floor level according to type examination and Machine Directive 2006/42/EC

See catalogue SKG „Service lifts“, pages 82 to 83 and 86 to 87

PROJECT

Client: _____

Project: _____

Date: _____ Request: _____

GENERAL

Capacity: 1500 kg 2000 kg Safety gear: Yes

Chargement: Front-loading Through-loading

Position of machine room: on top

Number of stops: _____ Number of landings: _____ Floor markings: _____

Power supply: 3 x 400 V 50 Hz 3 x 380 V 50 Hz 3 x 230 V 50 Hz

Others: _____

Shaft (Floor to floor distances see in supplement for floor to floor distances)

Width: _____ mm Depth: _____ mm Travel: _____ mm Headroom: _____ mm Pit: _____ mm

Cabin

Width: _____ mm Depth: _____ mm Height: _____ mm


FINISHES

	Cabin	Landing doors	Machine room door
Gavanized	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stainless steel 1.4016 (AISI 430) brushed grain K240	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stainless steel 1.4301 (AISI 304) brushed grain K240	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stainless steel 1.4301 (AISI 304) 5WL	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stainless steel 1.4571 (AISI 316Ti) brushed grain K240	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Other finishes: _____


Inquiry form for the SKG-service lift ISO-PE EASY 1500/2000

Goods lift with one accompanying person / Swing doors serving at floor level according to type examination and Machine Directive 2006/42/EC



Please check the floors.

1	2	3	4	5	6	7	8
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>



1	2	3	4	5	6	7	8
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Please check the floors.

Inquiry form for the SKG-service lift **ISO-PE EASY 1500/2000**

Goods lift with one accompanying person / Swing doors serving at floor level according to type examination and Machine Directive 2006/42/EC

OPTIONS

Shaft

Ladder: Yes with anti-theft device

Lightning: Yes No

Landing doors

Fire certificate: EN81-58 E120 EW60/EW30 (only at door with ≤ 1500 mm)

EN81-58 EI60 (only at door with ≤ 1000 mm)

Machine room door

Double walls: Yes additionally with mineral wool

Fire certificate: EN81-58 E120 EW60 (only at door with ≤ 1500 mm)

EN81-58 EI60 (only at door with ≤ 1000 mm)

Safety lock: with profile cylinder with KABA cylinder (for Switzerland only)

Electrical:

Lockable push button stations: with profile cylinder with KABA cylinder (for Switzerland only)

Other equipment: